



K44 Duo Codelock with 30 codes

Access Control

-
- Programmable codelock for two doors
 - Sturdy construction for outdoor and indoor use
 - Alarm output
 - Up to 20 codes can be used

The K44 is a programmable codelock for two doors, with two-relay outputs and the possibility to set separate codes for each door or the same code for both. There is also an option of door control with alarm output. The K44 has a code capacity of twenty 4-digit codes and ten 6-digit codes.

Technical data

| K44 Duo | |
|------------------------|---|
| Housing | Cast metal with stainless steel buttons and security lock |
| Colour | Grey |
| Environment | Indoor or outdoor use (IP54 design). In very exposed locations, use SH2 or SH1 rain cover. |
| IP rating | IP54 |
| Operating temperature | -35 to +55 °C |
| Operating voltage | 10 to 35 VDC 8 to 24 VAC |
| Current consumption | 75 mA in standby |
| Dimensions (W x H x D) | 80 x 140 x 40 mm |
| Door capacity | 2 |
| Code capacity | Twenty 4-digit codes and ten 6-digit codes |
| Inputs | Two exit button requests with delay. Two separate for codes disable. Two for door contacts. External control of zero opening. |
| Outputs | Two voltage-free relay contacts, max. 2 A, 28 VDC. Open collector for duress/alert. Open collector for door bell. Tamper switch for alarm connection (normally closed). |
| Opening time | 1-99 seconds programmable from keypad |

Details for ordering

| Type | Part no | Designation | Weight |
|---------|-----------------|------------------------|---------|
| K44 Duo | S24246-C3553-A1 | Codelock with 30 codes | 0.80 kg |

Issued by
Bewator AB
SE-171 24 Solna
Sweden

www.buildingtechnologies.siemens.com

© 2008 Copyright by
Bewator AB, a Siemens company
Data and design subject to change without notice.
Supply subject to availability.

Document no. **A6V10081456**
Edition 04.2008